



Just imagine

AMANA BY DESIGN

Amana®

TECHNICAL SPECIFICATIONS

Amana cladded sxs

	Model	Definition						
		224FNRS	224DNRS	228FIRS	228DIRS	626FIRS	626DIRS	
	Model Number	Fully Clad Stainless Steel no Ice	Stainless Steel Doors and Black Sides no Ice	Fully Clad Stainless Steel with Ice	Stainless Steel Doors and Black Sides with Ice	Fully Clad Stainless Steel with Ice	Stainless Steel Doors and Black Sides with Ice	Fully Clad Stainless Steel No Ice
	Description							
performance	Capacity (cu. ft.) Litres Gross / Net	(21.5) 625 / 616	(21.5) 625 / 616	(21.57) 610 / 594	(21.57) 610 / 594	(25.6) 712 / 693	(25.6) 712 / 693	(21.5) 625 / 616
	Fresh Food Capacity (cu. ft.) Litres Gross / Net	(13.51) 395 / 386	(13.51) 395 / 386	(13.48) 395 / 386	(13.48) 395 / 386	(15.83) 454 / 446	(15.83) 454 / 446	(13.51) 395 / 386
	Freezer Capacity (cu. ft.) Litres Gross / Net	(7.96) 230 / 230	(7.96) 230 / 230	(8.09) 215 / 208	(8.09) 215 / 208	(9.77) 258 / 247	(9.77) 258 / 247	(7.96) 230 / 230
	Total Shelf Area (sq. ft.)	20.7	20.7	18.4	18.4	22.7	22.7	20.7
	Energy Class / Climate Class / KWH per year / DBA	A / T / 584 / 44	A / T / 584 / 44	A / T / 593 / 44	A / T / 593 / 44	A / T / 635 / 44	A / T / 635 / 44	A / T / 584 / 44
	Freezing Capacity	13.1	13.1	12	12	13.4	13.4	13.1
	Star Rating of Freezer	****	****	****	****	****	****	****
	Four Point Levelling System	•	•	•	•	•	•	•
	Voltage / Hertz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz
system controls	Control System	Electronic	Electronic	Fully Electronic	Fully Electronic	Fully Electronic	Fully Electronic	Electronic
	Water / Ice Filter			•	•	•	•	
	Water Filter Indicator – On Controls			•	•	•	•	
	Water			•	•	•	•	
	Cubed Ice			•	•	•	•	
	Crushed Ice			•	•	•	•	
	Dispenser Lock			•	•	•	•	
	Dispenser Light (Manual / Auto)			•	•	•	•	
	Beverage Chiller	•	•	•	•	•	•	•
Mini Chiller			•	•	•	•		
dimensions	A Cabinet Height: With Hinge (mm)	1780	1780	1780	1780	1780	1780	1840
	B Cabinet Width: (mm)	915	915	915	915	915	915	915
	Cabinet Depth: Without Door (mm)	599	597	599	597	713	711	599
	C Cabinet Depth: With Door (mm)	669	668	669	668	772	771	669
	Depth with Door Open to 90 degrees	1158	1158	1158	1158	1258	1258	1158
	Distance from side wall to allow 90 degree door opening (excluding handle)*	50	50	50	50	50	50	50
	Carton H x W x D (mm)	1822 x 1003 x 813	1822 x 1003 x 813	1822 x 1003 x 813	1822 x 1003 x 813	1816 x 997 x 864	1816 x 997 x 864	1822 x 1003 x 813
	Approximate Shipping Weight (kgs)	196	151	196	151	216	200	197
	Anti-bacterial Protection	•	•	•	•	•	•	•
	Auto Defrost	•	•	•	•	•	••	•
	Average Annual Energy Cost	£40.88	£40.88	£41.51	£41.51	£44.45	£44.45	£40.88
	Fast Freeze			•	•	•	•	
	Freezer Shelves	5	5	2	2	2	2	5
	Fridge Position	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side
Fridge Shelves	4	4	4	4	4	4	44	
Frost Free	•	•	•	•	•	•	•	
Freezer Lights	•	•	•	•	•	•	•	
Tilting Door Baskets – Freezer	•	•	•	•	•	•	•	
Optional Ice Maker	•	•					•	
Fully Extendable Crisper Drawers			•	•	•	•		
Fully Extendable Freezer Baskets			•	•	•	•		
Humidity Controlled Crisper Drawers	•	•	•	•	•	•	•	
Temperature Controlled Meat and Cheese Drawer	•	•	•	•	•	•	•	
Refrigerator Lights	•	•	•	•	•	•	•	
Fitted Trim Kit for 6mm Panels	•	•	•	•	•	•	•	
Power Cut Safe Time	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	
Temperature Indicator			•	•	•	•		

* Removing the shelves and drawers requires the doors to be open wider than 90 degrees

Please refer to the dimension drawings on page 7 and the Expert Advice notes on page 8.

Amana cladded SXS continued

Precision						Reflection					
224DNRS	228FIRS	228DIRS	626FIRS	626DIRS	224FNRB / G	224DNRB / G	228FIRB / G	228DIRB / G	626FIRB / G	626DIRB / G	
Stainless Steel Doors and Black Sides no Ice	Fully Clad Stainless Steel with Ice	Stainless Steel Doors and Black Sides with Ice	Fully Clad Stainless Steel with Ice	Stainless Steel Doors and Black Sides with Ice	Fully Clad Stainless Steel Black or Grey Glass no Ice	Stainless Steel, Black / Grey Glass Black Sides no Ice	Fully Clad Stainless Steel Black or Grey Glass with Ice	S/S, Black or Grey Glass Doors Black Sides with Ice	Fully Clad S/Steel, Black or Grey Glass with Ice	S/S, Black or Grey Glass Doors Black Sides, with Ice	
(21.5) 625 / 616	(21.57) 610 / 594	(21.57) 610 / 594	(25.6) 712 / 693	(25.6) 712 / 693	(21.5) 625 / 616	(21.5) 625 / 616	(21.57) 610 / 594	(21.57) 610 / 594	(25.6) 712 / 693	(25.6) 712 / 693	
(13.51) 395 / 386	(13.48) 395 / 386	(13.48) 395 / 386	(15.83) 454 / 446	(15.83) 454 / 446	(13.51) 395 / 386	(13.51) 395 / 386	(13.48) 395 / 386	(13.48) 395 / 386	(15.83) 454 / 446	(15.83) 454 / 446	
(7.96) 230 / 230	(8.09) 215 / 208	(8.09) 215 / 208	(9.77) 258 / 247	(9.77) 258 / 247	(7.96) 230 / 230	(7.96) 230 / 230	(8.09) 215 / 208	(8.09) 215 / 208	(9.77) 258 / 247	(9.77) 258 / 247	
20.7	18.4	18.4	22.7	22.7	20.7	20.7	18.4	18.4	22.7	22.7	
A/T / 584 / 44	A / T / 593 / 44	A / T / 593 / 44	A / T / 635 / 44	A / T / 635 / 44	A / T / 584 / 44	A / T / 584 / 44	A / T / 593 / 44	A / T / 593 / 44	A / T / 635 / 44	A / T / 635 / 44	
13.1	12	12	13.4	13.4	13.1	13.1	12	12	13.4	13.4	
****	****	****	****	****	****	****	****	****	****	****	
.	
220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	
Electronic	Fully Electronic	Fully Electronic	Fully Electronic	Fully Electronic	Electronic	Electronic	Fully Electronic	Fully Electronic	Fully Electronic	Fully Electronic	
.	
.	
.	
.	
.	
.	
.	
.	
.	
.	
1840	1840	1840	1840	1840	1780	1780	1780	1780	1780	1780	
915	915	915	915	915	915	915	915	915	915	915	
597	599	597	713	711	599	597	599	597	713	711	
668	669	668	772	771	675	674	675	674	785	783	
1158	1158	1158	1258	1258	1158	1158	1158	1158	1258	1258	
50	50	50	50	50	60	60	60	60	60	60	
1822 x 1003 x 813	1822 x 1003 x 813	1822 x 1003 x 813	1816 x 997 x 864	1816 x 997 x 864	1822 x 1003 x 813	1822 x 1003 x 813	1822 x 1003 x 813	1822 x 1003 x 813	1816 x 997 x 864	1816 x 997 x 864	
196	196	152	217	202	196	151	196	151	216	200	
.	
.	
£40.88	£41.51	£41.51	£44.45	£44.45	£40.88	£40.88	£41.51	£41.51	£44.45	£44.45	
.	
5	2	2	2	2	5	5	2	2	2	2	
Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	Right Hand Side	
4	4	4	4	4	4	4	4	4	4	4	
.	
.	
.	
.	
.	
.	
.	
.	
7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	7 hours	
.	

Please refer to the dimension drawings on page 7 and the Expert Advice notes on page 8.

Amana cladded 3D

Models	Definition		Precision		Reflection	
	320FNRS	320DNRS	320FNRS	320DNRS	320FNRB/G	320DNRB/G
Model Number	320FNRS	320DNRS	320FNRS	320DNRS	320FNRB/G	320DNRB/G
Description	Fully Cladded Stainless Steel	Stainless Steel Doors Only with Black Sides	Fully Cladded Stainless Steel	Stainless Steel Doors Only with Black Sides	Fully Cladded Stainless Steel with Black or Grey Glass	Stainless Steel Doors Only, Black or Grey Glass, Black sides
performance	Capacity (cu. ft.) Litres Gross / Net	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559
	Fresh Food Capacity (cu. ft.) Litres Gross / Net	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406
	Freezer Capacity (cu. ft.) Litres Gross / Net	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153
	Total Shelf Area (sq. ft.)	16.9	16.9	16.9	16.9	16.9
	Energy Class / Climate Class / KWH per year / DBA	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44
	Freezing Capacity	10.2	10.2	10.2	10.2	10.2
	Star Rating of Freezer	****	****	****	****	****
	Four Point Levelling System	•	•	•	•	•
	Voltage / Hertz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz
	Control System	Electronic	Electronic	Electronic	Electronic	Electronic
dimensions	A Cabinet Height: With Hinge (mm)	1780	1780	1840	1840	1780
	B Cabinet Width: (mm)	915	915	915	915	915
	Cabinet Depth: Without Door (mm)	599	597	599	597	599
	C Cabinet Depth: With Door (excluding handles) (mm)	668	668	668	668	668
	Depth with Door Open to 90 degrees	1090	1090	1090	1090	1090
	Distance from side wall to allow 90 degree door opening (excluding handle)*	50	50	50	50	60
	Carton H x W x D (mm)	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815
	Approximate Shipping Weight (kgs)	201	156	202	157	201
extra features	Anti-bacterial Protection	•	•	•	•	•
	Auto Defrost	•	•	•	•	•
	Average Annual Energy Cost	£36.26	£36.26	£36.26	£36.26	£36.26
	Fridge Position	Top	Top	Top	Top	Top
	Fridge Shelves	4	4	4	4	4
	Frost Free	•	•	•	•	•
	Humidity Controlled Crisper Drawers	•	•	•	•	•
	Temperature Controlled Meat and Cheese Drawer	•	•	•	•	•
	Refrigerator Lights	•	•	•	•	•
	Freezer Lights	•	•	•	•	•
	Optional Ice Maker	•	•	•	•	•
	Freezer Baskets	2	2	2	2	2
	Power Cut Safe Time	7 Hours	7 Hours	7 Hours	7 Hours	7 Hours
Temperature Indicator	•	•	•	•	•	

* Removing the shelves and drawers requires the doors to be open wider than 90 degrees

Please refer to the dimension drawings on page 7 and the Expert Advice notes on page 8.

Amana cladded bxm

	Models	Definition		Precision		Reflection	
		026FNRSRL / R	026DNRSRL / R	026FNRSRL / R	026DNRSRL / R	026FNRBL / R & 026FNRGL / R	026DNRBL / R & 026DNRGL / R
	Model Number	026FNRSRL / R	026DNRSRL / R	026FNRSRL / R	026DNRSRL / R	026FNRBL / R & 026FNRGL / R	026DNRBL / R & 026DNRGL / R
	Description	Fully Cladded Stainless Steel	Stainless Steel Doors Only with White Sides	Fully Cladded Stainless Steel	Stainless Steel Doors only with White Sides	Fully Cladded Stainless Steel with Black or Grey Glass	Stainless Steel Doors Only, Black or Grey Glass, White Sides
performance	Capacity (cu. ft.) Litres Gross / Net	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559	(19.9) 568 / 559
	Fresh Food Capacity (cu. ft.) Litres Gross / Net	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406	(14.4) 411 / 406
	Freezer Capacity (cu. ft.) Litres Gross / Net	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153	(5.5) 157 / 153
	Total Shelf Area (sq. ft.)	16.9	16.9	16.9	16.9	16.9	16.9
	Energy Class / Climate Class / KWH per year / DBA	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44	A / T / 518 / 44
	Temp Rise – Hours	16.7	16.7	16.7	16.7	16.7	16.7
	Freezing Capacity	10.2	10.2	10.2	10.2	10.2	10.2
	Star Rating of Freezer	****	****	****	****	****	****
	Four Point Levelling System
SYS CONT	Voltage / Hertz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz
	Control System	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
dimensions	Beverage Chiller
	A Cabinet Height: With Hinge (mm)	1785	1785	1852	1852	1785	1785
	B Cabinet Width: (mm)	910	910	910	910	910	910
	Cabinet Depth: Without Door (mm)	599	597	599	597	599	597
	C Cabinet Depth: With Door (excluding handles) (mm)	668	667	668	667	675	675
	Depth with Door Open to 90 degrees	1545	1545	1545	1545	1545	1545
	Distance from side wall to allow 90 degree door opening (excluding handle)*	50	50	50	50	60	60
	Carton H x W x D (mm)	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815	1815 x 997 x 815
	Approximate Shipping Weight (kgs)	200	156	201	156	201	156
extra features	Anti-bacterial Protection
	Auto Defrost
	Average Annual Energy Cost	£36.26	£36.26	£36.26	£36.26	£36.26	£36.26
	Fridge Position	Top	Top	Top	Top	Top	Top
	Fridge Shelves	4	4	4	4	4	4
	Frost Free
	Humidity Controlled Crisper Drawers
	Temperature Controlled Meat and Cheese Drawer
	Refrigerator Lights
	Freezer Lights
	Optional Ice Maker
	Freezer Baskets					2	2
	Power Cut Safe Time	7 Hours	7 Hours	7 Hours	7 Hours	7 Hours	7 Hours
Temperature Indicator	

* Removing the shelves and drawers requires the doors to be open wider than 90 degrees
Hinge position is available in both left and right options and is denoted in the model number ie: Definition 026FNRSRL denotes the hinge position to be on the left while Definition 026FNRSR denotes that the hinge position is on the right.

Please refer to the dimension drawings on page 7 and the Expert Advice notes on page 8.

Amana wine cabinets

Models		Definition Wine	Precision Wine		Reflection Wine	
Model Number		W208SS	W208SS	W208CG	W208SB	W208CG
Description		Stainless Steel Sides and Door	Stainless Steel Sides and Door	S/Steel Sides with Clear Glass Door	S/Steel Sides with Black Glass Door	S/Steel Sides with Clear Glass Door*
performance	Total Bottle Capacity	172 to 208	172 to 208	172 to 208	172 to 208	172 to 208
	Total Shelf Area (m²)	3.68	3.68	3.68	3.68	3.68
	Climate Class / KWH Per Year	Temperate / 328	Temperate / 328	Temperate / 328	Temperate / 328	Temperate / 328
	Four Point Levelling System	•	•	•	•	•
	Voltage / Hertz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz	220 – 240V / 50Hz
system controls	Room Temperature (Upper Compartment) On / Off Button	•	•	•	•	•
	Room Temperature (Upper compartment) Temperature Display	•	•	•	•	•
	Main Storage Area Temperature Heating Control	•	•	•	•	•
	Main Storage Area Temperature Display	•	•	•	•	•
	Main Storage Area Temperature Cooling Control	•	•	•	•	•
	Circuit Tester	•	•	•	•	•
	Cabinet On / Off Switch	•	•	•	•	•
dimensions	A Cabinet Height: With Hinge (mm)	1830	1880	1880	1830	1830
	B Cabinet Width: (mm)	685	685	685	685	685
	C Cabinet Depth: Without Door (mm)	590	590	590	590	590
	Cabinet Depth: With Door (excluding handles) (mm)	650	650	650	650	650
	Depth with Door Open to 90 degrees	1280	1280	1280	1280	1280
	Hinge Position	Right	Right	Right	Right	Right
	Distance from Side Wall to allow 90 degree door opening (excluding handle)**	50	50	50	50	50
	Approximate Shipping Weight (kgs)	157kg	158kg	160kg	160kg	160kg
extra features	Door Material	Stainless Steel	Stainless Steel	Clear Glass	Black Opaque Glass	Clear Glass
	Number of Temperature Zones	3	3	3	3	3
	Number of Shelves	12	12	12	12	12
	Shelf Material	Beech	Beech	Beech	Beech	Beech
	Bottle Capacity Per Shelf	13	13	13	13	13
	Bottle Capacity Upper Compartment	11	11	11	11	11
	Bottle Capacity Main Storage Area	156 to 191	156 to 191	156 to 191	156 to 191	156 to 191
	Bottle Capacity Lower Compartment	6	6	6	6	6

* Will also match the Definition range, if clear glass door is wanted

** Removing the shelves and drawers requires the doors to be open wider than 90 degrees

For ventilation, it is necessary to allow an extra 25mm of space at the rear of the wine cabinet.

Please refer to the dimension drawings on page 7 and the Expert Advice notes on page 8.

We suggest that you allow the wine cabinet to rest in place for 48 hours before switching on.



Amana base models

Panel kit panel sizes

	Model	Side by Side			Bottom Mount
		AC2224PEKB/W	AC2228HEKB/W	AS2628HEKB	GB2026PEKB/W
	Model Number	AC2224PEKB/W	AC2228HEKB/W	AS2628HEKB	GB2026PEKB/W
	Description	Black or White no Ice	Black or White with Ice	Black with Ice	Black or White no Ice
performance	Capacity (cu. ft.) Litres Gross/Net	(21.5) 625/616	(21.57) 610/594	(25.6) 712/693	(19.9) 568/559
	Fresh Food Capacity (cu. ft.) Litres Gross/Net	(13.51) 395/386	(13.48) 395/386	(15.83) 454/446	(14.4) 411/406
	Freezer Capacity (cu. ft.) Litres Gross/Net	(7.96) 230/230	(8.09) 215/208	(9.77) 258/247	(5.5) 157/153
	Total Shelf Area (sq. ft.)	20.7	18.4	22.7	16.9
	Energy Class/Climate Class/KWH per year/DBA	A/T/584/44	A/T/593/44	A/T/635/44	A/T/518/44
	Freezing Capacity	13.1	12	13.4	10.2
	Star Rating of Freezer	****	****	****	****
	Four Point Levelling System	•	•	•	•
	Voltage / Hertz	220 – 240V/50Hz	220 – 240V/50Hz	220 – 240V/50Hz	220 – 240V/50Hz
	Control System	Electronic	Fully Electronic	Fully Electronic	Electronic
system controls	Water /Ice Filter		•	•	
	Water Filter Indicator – On Controls		•	•	
	Water		•	•	
	Cubed Ice		•	•	
	Crushed Ice		•	•	
	Dispenser Lock		•	•	
	Dispenser Light (Manual/ Auto)		•	•	
	Beverage Chiller	•	•	•	•
	Mini Chiller		•	•	
dimensions	A Cabinet Height: With Hinge (mm)	1778	1778	1778	1780
	Cabinet Height: Without Hinge (mm)	1740	1740	1740	1743
	B Cabinet Width: (mm)	905	905	905	905
	Cabinet Depth: Without Door (mm)	597	597	711	597
	C Cabinet Depth: With Door (mm)	679	679	781	654
	Depth with door open to 90 degrees	1156	1156	1258	1156
	Distance from side wall to allow 90 degree door opening *	45	45	45	45
	Carton H x W x D (mm)	1822 x 1003 x 813	1822 x 1003 x 813	1816 x 997 x 864	1815 x 997 x 815
	Approximate Shipping Weight (kgs)	136	136	156	141
	Anti-bacterial Protection	•	•	•	•
extra features	Auto Defrost	•	•	•	•
	Average Annual Energy Cost	£40.88	£41.51	£44.45	£36.26
	Fast Freeze		•	•	
	Freezer Shelves	5	2	2	
	Fridge Position	Right Hand Side	Right Hand Side	Right Hand Side	Top
	Fridge Shelves	4	4	4	4
	Frost Free	•	•	•	•
	Freezer Lights	•	•	•	•
	Tilting Door Baskets – Freezer	•	•	•	
	Optional Ice Maker	•			•
	Fully Extendable Crisper Drawers		•	•	•
	Fully Extendable Freezer Baskets		•	•	•
	Humidity Controlled Crisper Drawers	•	•	•	
	Temperature Controlled Meat and Cheese Drawer	•	•	•	•
	Refrigerator Lights	•	•	•	
	Fitted Trim Kit for 6mm panels	•	•	•	•
	Power Cut Safe Time	7 hours	7 hours	7 hours	7 Hours
	Temperature Display		•	•	


* Removing the shelves and drawers requires the doors to be open wider than 90 degrees

	Model	Side by Side			Bottom Mount
		AC2224PEKB/W	AC2228HEKB/W	AS2628HEKB	GB2026PEKB/W
panel sizes	Refrigerator Door (H) x (W) mm	1695 x 481	1695 x 481	1695 x 481	n/a
	Freezer Door Upper (H) x (W) mm	n/a	460 x 354	460 x 354	n/a
	Freezer Door Lower (H) x (W) mm	n/a	815 x 354	815 x 354	n/a
	Freezer Door (H) x (W) mm for	1695 x 354	n/a	n/a	n/a
	Upper Door (H) x (W) mm	n/a	n/a	n/a	1068 x 905.8
	Lower Door (H) x (W) mm	n/a	n/a	n/a	590.6 x 916.9
	Trim Kit Panel Fixing Kit, Stainless Steel Handles	HT204	HT204	HT204	HTK531S
	Trim Kit Panel Fixing Kit, Black Handles	HTBK204	HTBK204	HTBK204	HTK531B
	Dispenser for use with Panel Kit	n/a	BFNK4B/W	BFNK4B/W	n/a
	Perimeter Kit BxM depends on hinging position	Perimeter Kit SXS	Perimeter Kit SXS	Perimeter Kit SXS	Perimtr Kit BxML, or BxMR




Please refer to the dimension drawings on page 7 and the Expert Advice notes on page 8.


reflection




Reflection 320FNRB
3D Black



Reflection 228FIRB
SxS Black




Reflection 026FNRB
BxM Black




Reflection Wine
Cabinet Black


definition




Definition 320FNRS
3D



Definition 228FIRS
SxS




Definition 026FNRSR
BxM




Definition Wine
Cabinet


precision




Precision 320FNRS
3D



Precision 228FIRS
SxS



Precision 026FNRSR
BxM



Precision Wine
Cabinet

finishing TOUCHES

Every Amana Refrigerator is a class-leading appliance ...superbly built and fitted with a host of features that are either aesthetically beautiful, hugely practical...or both! Even so, we all have different requirements in terms of day-to-day use, so you can also choose from a range of optional accessories to make your Amana even more individual to you.

You can opt for square handles instead of round, or vice versa...not just when you buy your appliance, but later if your design scheme changes or you move to a different house. Icemakers can be retro-fitted to the freezer drawers of all BxM and 3D models, and to the 22 cu.ft. and 26 cu.ft. 'non ice and water' models. You can always add extra shelves, chillers or drawers. And when the indicator light tells you the filter for your ice and water dispenser needs replacing, that's easy too. Simply contact Customer Care on 01737 231 000 or your nearest stockist.



ROUND HANDLES



SQUARE HANDLES



WATER FILTER

expert ADVICE

If you're planning to integrate your Amana appliance into kitchen cabinetry, it's important to seek expert guidance from professionals, particularly during the design process. They will be able to advise you on the subtle nuances of design and on the practical issues that arise from the relative positioning of appliances, cabinetry and other kitchen features. The photographs and specifications in this brochure have been provided to inspire your choice and to help in the planning process. Remember to treat them as a guide, but always refer to the installation instructions that accompany each product before selecting cabinetry, making cut-outs or beginning installation. This way your kitchen will be... perfection itself.



Please allow 10mm on each side and 25mm on the top to allow adequate ventilation and ease of installation. Heights may vary slightly due to levelling adjustments.

For appliances with ice and water dispensers, allow an extra 25mm at the rear for plumbing connections. They also require a water pressure connection of between 30 and 120psi.

All refrigeration models require an ambient temperature of between 10°C and 43°C to function correctly. We suggest that you allow the wine cabinet to rest in place for 48 hours before switching on.

E&OE.



Amana®

AMANA - 2 ST ANNE'S BOULEVARD,
FOXBORO BUSINESS PARK, REDHILL, SURREY. RH1 1AX

T. +44 (0) 1737 231 000 F. +44 (0) 1737 778 822

E. info.uk@amana.com www.amana.co.uk